

Asset-Tracking References (TRK)

			LoRaWAN	Flanges	IP Index
TRK-TRACER	TRK-INO-MAIR-X89-510	TRK-Tracer - 868/915	868/915	•	IP54
	TRK-INO-MAIR-X89-610	TRK-Tracer - 868/915	868/915	•	IP66
	TRK-INE-MAIR-X89-510	TRK-Tracer - 868/915	868/915	-	IP54
	TRK-INE-MAIR-X89-610	TRK-Tracer - 868/915	868/915	-	IP66
Variante	GPS	TRK-INO-GPMAIR-X89-610	868/915	•	IP66
	Slim	TRK-SLI-MAPB-X89-460	868/915	X	IP44
TRK-ZON	TRK-ZON-MAIR-X89-640	TRK-Zon - Long life battery	868/915	x	IP66

OPTION WITH/WITHOUT FLANGES	
With	•
Without	-
Different case	X



CAUTION: THIS PRODUCT USES LITHIUM BATTERIES.

For your safety, please check our website.

Customizations on request.

Contact us for more information.

INEO-SENSE

125 Rue de L'hostellerie,
Immeuble ELLIPSIS, Niv 4 Porte 12
30 900 Nîmes — France

Tel: +33 466 276 495
Web : www.ineo-sense.com
contact@ineo-sense.com